

GIRAFFE RATTLE

This done in a frame 10x10cm

You will have 3 steps in 10x10cm

1-Ears

2-The head

3-The ring

For the bandana, it is done in a hoop of 13x18 but you can do it in the sewing machine with the pattern attached.

Hardware:

I did with Minky

You will need 3 colors of minky, white, pale yellow, white or pale beige and yellow for the ring.

For the bandana, 2 pieces of 14cm x 7.5cm

Hypoalergen wad, Bandana snap, water-soluble support

FIRST STEP:

I start by making the ears, muzzle and ossicones, I always work out of frame, you can take the temporary glue to help you

First step put your support in your frame 10x10cm. Follow the steps on the worksheet that is with your file in .PDF

- 1- The first seam must be done on the support to tell you where to put your fabric, be careful to hide this seam with your fabric. At each step, I take the measure that I need material to cover the seam
- 2- The second seam is done on your fabric to sew your fabric on your support
- 3 Embroidery on ossicones
- 4- For the next step, put your piece of fabric on the back of the frame at the exact place of your piece of fabric that is on the place of your frame, this seam will join the back and front of the ossicones







- 5- Sewing to show you the location of your fabric for the ears, take the measurement and put your fabric over this seam before moving on to the next step
- 6 Sewing the fabric of the ears on your support
- 7 Sewing to tell you where to put your fabric for the inside of the ears
- 8 Seam your piece for the inside of the ears, once this seam is finished, remove the excess fabric. Take your piece of fabric for the back of the ears, put this piece place against place on your ear part work and move on to the next step
- 9- Back seam with front for ears



the muzzle, put and support to the



10-Sewing done on your support to tell you location of the take the measurement and your piece of fabric your water-soluble before moving on next step

11-Point of embroidery, once your embroidery stitches are finished, remove your hydrosolubl e support, take your piece for the back of the muzzle and put it on your piece in front, place against place,

12-Seam the front and back of the muzzle together, notice that the seam is complete





It remains only to get out of the frame, clean the ossicones, for the muzzle, it is necessary to make a small opening of the part of the fabric that is on the reverse, from this opening you can turn your piece. M be sideways until it is time to make the head.





THE RING:

- 1 STOP 1: This fact on the support to tell you where to put your fabric, put your fabric on your support to hide the seam
- 2- STOP 2: this seam is used to hold your fabric on your frame, once this seam is finished, put your piece of fabric, place against place.
- 3 STOP 3: This seam is used to join your two pieces of fabric together. When finished, get out of your frame, cut where there is no a No sewing, be careful to cut in the right place. Remove excess fabric, return to the place, fill with stuffing and make an invisible seam for Putting it both together. Link to know how to make an invisible seam:

Putting aside time to make the head









THE HEAD:

- 1 Sewing on your stand to show you the size of the head when finished
- 2- Seam to show you the location of your fabric for the upper face (pale yellow part)
- 3 Sewing your fabric on your support, once this seam is finished, remove the excess fabric and take your **water-soluble** support and put it on your piece of fabric before moving on to embroidery
- 4- Track colors for embroidery stitches
- 5 Seam to tell you the location of the muzzle
- 6 Sewing of the muzzle part on your support, cut the excess fabric on the top of the muzzle.
- 7 Couture to tell you the location of the ears and ossicones
- 8 Put your ear place against place and hold well in place, do the sewing of your ear
- 9- Do the same steps for the ossicones and the other ear.
- 10- Once theears and ossicones are finished, take a piece of fabric of 11x11cm for the back of the head, put place against place on your project, this seam will bring together the front and back of the head

Get out of the frame, cut the excess fabric and turn over





THE BANDANA:

You have 2 methods to do it, either in a 13x18cm frame or print the pattern that I provide you and do it with the sewing machine.

For my part I prefer to do it with the sewing machine. If you want to do it with the embroidery machine, stop 1 this fact on the support to tell you where to put your fabric. Put your fabric and make stop 2 that will fix your fabric on your support. When this seam is finished, take your second piece and put it place against place on your fabric that is on your support, stop 3: assembly of your 2 pieces.

Remove from your support, cut the excess fabric and flip, make the small seam in the top to close the bandana completely and put the snaps.

ASSEMBLY:

All you have to do is make the assembly, the ring should already be closed, For the head, position it on the seam of your ring, I put a little fabric glue to hold the head in place until I can do the invisible seam.

Once the head is set up, take the muzzle, with fabric glue, stick the muzzle on the face, once well in place, sew with an invisible seam by matching the 2 muzzles together, all that remains is to put his bandana and here you have a beautiful rattle that is safe for children.

PS: I always do at least 3 times the invisible seam so that it is really well sewn.